

REVISED DRAFT QRs AND TDs FOR HOOK AND LINE SET

S No	Parameters	QR	TD
1.	Physical Characteristics	(a) It should be easily carried and require minimum maintenance	To be physically checked by BOO.
		(b) It should be operative in all weather and easy to use	-do-
		(c) Rugged metal should be used	-do-
2.	Technical Requirements	(a) Reel Assembly 300 mm dia with handle and should hold the line provided with kit – 02 Nos	-do-
		(b) Line to be 5.5mm dia and 120m length – 02 Nos	-do-
		(c) Pulling handle – 02 Nos	-do-
		(d) Hooks:-	-do-
		(i) Single plain 12mm - 02 Nos	-do-
		(ii) Single plain 25mm - 02 Nos	-do-
		(iii) Single plain 50mm - 02 Nos	-do-
		(iv) Double plain 25mm - 02 Nos	-do-
		(v) Double plain 50mm- 02 Nos	-do-
		(vi) Single barded 25mm - 02 Nos	-do-
		(vii) Single barded 50mm - 02 Nos	-do-
		(viii) Single barded 12mm - 02 Nos	-do-
		(ix) Double barded 25mm - 02 Nos	-do-
		(x) Double barded 50mm - 02 Nos	-do-
		(xi) Spring gate hook - 01 Nos	-do-
		(xii) Self-locking hook - 01 Nos	-do-
		(xiii) S hook - 01 No	-do-
		(e) Rod extension (Carbon Fiber) 3m - 01 No	-do-
		(f) Belt:-	-do-
		(i) 7.5 cm – 01 Nos	-do-
		(ii) 10 cm – 01 Nos	-do-
		(g) Snatch block self-opening – 04 Nos	-do-
		(h) Karabiners 25mm - 04 Nos	-do-
		(j) Pitons:-	-do-
		(i) 50mm – 06 Nos	-do-
		(ii) 100mm – 02 Nos	-do-
(k) Self-adhesive anchor – 10 Nos	-do-		
(l) Suction pad single and double; Single - 02 Nos and Double - 01 No	-do-		
(m) Telescopic pole with self-locking hook - 01 No	-do-		
(n) Grips:-	-do-		
(i) Spring- Max opening of 25mm – 01 No	-do-		
(ii) Vice – 01 No	-do-		
(o) Door stopper (Rubber) – 04 Nos	-do-		

S No	Parameters	QR	TD
		(p) Through wall anchor with ring – 01 No	To be physically checked by BOO
		(q) Rope Sling:-	-do-
		(i) 3mm diameter and 2m long - 02 Nos	-do-
		(ii) 5 mm diameter and 2 m long - 02 Nos	-do-
		(r) Wedge with eye – 02 Nos	-do-
		(s) Screw with eye – 10 Nos	-do-
		(t) Wire sling-1.5mm to 3mm diameter and 2 m long – 04 Nos	-do-
		(u) Pocket tool kit – 02 Nos	-do-
		(v) Search mirror (Foldable) - 01 No	-do-
		(w) Door way anchor min 700-1100 mm with eyes - 02 Nos	-do-
		(x) D Shackle at least 13mm gate and 1000 kg load - 02 Nos	-do-
		(y) Standard snatch block – 02 Nos	-do-
		(z) Ground Anchor – 06 Nos	-do-
		(aa) Webbing sling- 50mm width and (1m to 2m) length – 02 Nos	-do-
		(ab) Round sling:-	-do-
		(i) 1 m length – 02 Nos	-do-
		(ii) 3 m length – 02 Nos	-do-
		(iii) 5 m length – 02 Nos	-do-
		(ac) Snatch block heavy duty with swivel – 04 Nos	-do-
		(ad) Splitter ball – 02 Nos	-do-
		(ae) Snatch block, one way lock – 01 No	-do-
		(af) Fish hook – 02 Nos	-do-
		(ag) Hook 120mm opening fixed eye – 02 Nos	-do-
		(ah) Remote window breaker – 01 No	-do-
		(aj) Seizer lock Jaw 85mm length 175mm – 01 No	-do-
		(ak) Tripod lifting capacity minimum 250 kg & minimum 2 m – 01 No	-do-
3.	Ease of Use	(a) The items should be housed in a rugged carrying case fitted with rubberized foam and rollers for easy transport.	-do-